

# Locating XML Documents in a Peer-to-Peer Network Using Distributed Hash Tables

Praveen R. Rao, *Member, IEEE Computer Society*, and Bongki Moon

**Abstract**—One of the key challenges in a peer-to-peer (P2P) network is to efficiently locate relevant data sources across a large number of participating peers. With the increasing popularity of the extensible markup language (XML) as a standard for information interchange on the Internet, XML is commonly used as an underlying data model for P2P applications to deal with the heterogeneity of data and enhance the expressiveness of queries. In this paper, we address the problem of efficiently locating relevant XML documents in a P2P network, where a user poses queries in a language such as XPath. We have developed a new system called *psiX* that runs on top of an existing distributed hashing framework. Under the *psiX* system, each XML document is mapped into an algebraic signature that captures the structural summary of the document. An XML query pattern is also mapped into a signature. The query's signature is used to locate relevant document signatures. Our signature scheme supports *holistic processing* of query patterns without breaking them into multiple path queries and processing them individually. The participating peers in the network collectively maintain a collection of distributed hierarchical indexes for the document signatures. Value indexes are built to handle numeric and textual values in XML documents. These indexes are used to process queries with value predicates. Our experimental study on PlanetLab demonstrates that *psiX* provides an efficient location service in a P2P network for a wide variety of XML documents.

**Index Terms**—XML indexing, XPath, peer-to-peer computing, distributed hash tables.

## 1 INTRODUCTION

THE recent advances in peer-to-peer (P2P) computing have drawn much attention from researchers in various disciplines as well as users surfing the Internet. Although early P2P systems, such as Napster and Gnutella, made their debut as a music file sharing application and are still best known for similar file sharing services, P2P systems are gaining popularity rapidly in entrepreneurial sectors and scientific communities (e.g., the SEED project [1] for sharing genome data among biologists). These systems provide an infrastructure for a wide variety of applications that increasingly rely on decentralized computing, distributed and redundant storage, and self-organizing overlay networks.

Today, the extensible markup language (XML) has become the lingua franca for information representation and exchange over the Internet. Coupled with the growing popularity of P2P systems, XML is commonly used as a data model for P2P applications to overcome the limited expressiveness of queries and to deal with the underlying heterogeneity of data [2]. This is a natural and synergistic combination of XML and P2P, because XML provides a means to represent, index, and query semistructured data,

while P2P systems enable peers to share and locate data sources across the network.

Suppose users in a P2P network publish information such as bibliographies, items-for-sale, movie reviews, and personal profiles in XML format. A user can issue the following XQuery query to find the names of people who reside in Kansas City.

```
for $d in collection("P2P")
where $d/person[place="Kansas
City"]
return <res>$d/person/name/text()</res>
```

In the P2P network, this query can be processed in two phases. In the first phase, all the qualifying peers are located who store any XML document that has a match for the XPath expression `/person[place="Kansas City"]`. In the second phase, the query can be shipped to those qualifying peers and be executed on the matched XML documents, or the user can download these documents, and then, execute the query locally.

The past few years have witnessed tremendous research endeavors aimed at developing efficient query processing strategies for XML data. In the second phase of the example above, processing the XQuery query can be done efficiently by applying one of the many indexing and pattern matching strategies reported in the literature (e.g., XISS [3], TwigStack [4], and PRIX [5], [6]). Therefore, we shift the focus of this paper to the first phase of query processing and address the problem of locating all relevant XML documents across an Internet-scale P2P network. Formally, the problem that we address in this paper is stated as follows:

Suppose  $P$  denotes a set of peers and  $D$  denotes the set of XML documents published by peers. Given an XML query pattern  $q$ , determine, by *best-effort*, the set of documents  $D' \subseteq D$  such that  $q$  has a match in each document in  $D'$ , along with the peer that published it.

• P.R. Rao is with the Department of Computer Science and Electrical Engineering, University of Missouri-Kansas City, 550H Robert H. Flarshheim Hall, 5100 Rockhill Road, Kansas City, MO 64110-2499. E-mail: raopr@umkc.edu.

• B. Moon is with the Department of Computer Science, University of Arizona, PO Box 210077, Tucson, AZ 85721-0077. E-mail: bkmooon@cs.arizona.edu.

Manuscript received 4 Mar. 2008; revised 21 Oct. 2008; accepted 18 Dec. 2008; published online 8 Jan. 2009.

Recommended for acceptance by M. Garofalakis.

For information on obtaining reprints of this article, please send e-mail to: tkde@computer.org, and reference IEEECS Log Number TKDE-2008-03-0121. Digital Object Identifier no. 10.1109/TKDE.2009.26.

We adopt the notion of *best-effort* service, as is traditionally done in the Internet regarding the delivery of network traffic. In the problem statement, we mean by *best-effort* that a search is expected to find as many matching documents as possible. This is because some peers may not be reachable or may fail during query processing. In fact, distributed hash table (DHT) frameworks [7] rely on UDP (best-effort protocol) rather than TCP for key insert and lookup operations.

Our main challenge is to organize and index XML data in a distributed way such that the peers storing relevant XML data can be located, by contacting as few hosts in the network as possible. While our previous work on PRIX focused on finding all occurrences of a query pattern in XML documents, *psiX* aims to find relevant documents *by testing the existence of a query pattern* in the documents. Thus, storing and indexing the document summaries, which can be graphs, is sufficient. In this work, we focus purely on *XML pattern matching* and do not consider the use of different vocabularies for generating XML tag names, which may be required for ontology-based searching. The main contributions of this work are as follows:

- We propose a novel signature scheme to summarize XML documents. Each XML document is mapped into an *algebraic signature* that captures the structural summary of the document. A query pattern is also mapped into an *algebraic signature*. The existence of a pattern can be tested by dividing a document signature with a query signature. Our system supports *holistic matching* of a query pattern, which can contain “//” and wildcard “\*,” without breaking it into multiple simple path queries and processing them by issuing separate lookups.
- To quickly find matching documents, *psiX* organizes the document signatures in a collection (or forest) of distributed hierarchical indexes called *H-index*, built using DHTs. The index is decentralized and maintains itself gracefully under concurrent writes from different peers. In each hierarchical index (*H-index*), the document signatures of structurally similar documents tend to be grouped together in the same index node. As a result, while locating documents, few peers tend to be contacted. Value indexes are also built to handle numeric and textual values in XML documents and queries.
- We have performed the experimental evaluation of our proposed signature scheme and indexing strategy, using a rich heterogeneous collection of documents and queries in a P2P setup on PlanetLab [8]. We have compared *H-index* with an inverted index approach called *I-index*, which is similar to the one proposed by Galanis et al. [9], but stores document signatures instead of document paths.

## 2 BACKGROUND AND MOTIVATIONS

Several techniques have been proposed for indexing textual data, numeric data, and XML documents in P2P environments. For content-based full-text search, Tang et al. developed a P2P information retrieval system called *pSearch* [10], in which document semantics are computed by latent semantic indexing (LSI) [11] in a vector space.

Although LSI is an effective method for keyword-based information retrieval, it is not well suited to capture the hierarchical structure of XML documents.

Aberer et al. [12] proposed PGrid that builds a trie and clusters semantically similar data, thereby providing in-network indexing. BATON [13], a balanced tree overlay structure, was proposed to support exact match and range queries. Each node of the tree is stored on exactly one peer, and each node has links to its parent, children, adjacent nodes, and selected neighbors at the same level. P-Ring [14] proposes a P2P range index for efficiently supporting equality and range queries. It overcomes the probabilistic guarantees on searches and load balancing provided by PGrid, and the lack of load balancing guarantees in BATON. The above approaches are suitable for linearly ordered domains. However, an ordering of XML documents does not aid the process of twig pattern matching for locating relevant documents.

Viglas [15] proposed schemes to maintain distributed structures such as B<sup>+</sup>-trees and heap files in a DHT. Index nodes and heap pages are assigned random ids picked from the DHT's logical address space. They are then stored as key-value pairs. An index or a heap file is accessed by performing DHT lookup operations. Further, for B<sup>+</sup>-trees, a peer storing an index node is responsible for splitting it and can pick a random id for the newly created node. A local locking scheme has been suggested to support concurrent operations. A limitation of this approach is that the storing peer may not leave or fail when the splitting operation is being performed. Our *psiX* system also stores index nodes as key-value pairs in a DHT, but node ids are assigned deterministically. In fact, a storing peer can leave or fail during splitting.

P2P indexes have been proposed for multidimensional data [16], [17]. In these approaches, the entire multidimensional space is partitioned and merged as peers join and leave the P2P system. Liu et al.'s [16] approach relies on the existence of more powerful nodes called *superpeers* in the system. These indexes are not suitable for *psiX*, because XML document summaries are not mapped into a multidimensional space.

Next, we describe the techniques proposed for XML indexing and pattern matching in P2P environments. Sartiani et al. proposed a *superpeer*-based XML database system called XPeer [18]. More powerful peers take up extended responsibilities for a group of peers. Peers export a summary of their XML data in the form of a tree-shaped DataGuide [19]. Locating data sources is performed in a hierarchical way by matching a query twig with summaries, by traversing the superpeers organized to form a tree until any interesting location is detected. A superpeer-based approach is, however, not fully decentralized and requires special nodes.

Several approaches leverage a DHT that provides a fully decentralized overlay network. A distributed catalog framework was proposed for locating XML data sources in a P2P network [9]. Under this framework, element tags are chosen as keys. For each distinct tag, all unique element paths leading to the tag are stored in its data summary. All the key-summary pairs are stored in a DHT, in a similar way

that keys and instances are organized into an inverted list. For a given XPath path expression, the element tag at its leaf position is used as a lookup key in the DHT. Instead of element tags, paths can be used as keys. XP2P [20] also builds on a DHT framework and allows peers to store whole or fragments of XML documents locally, whose path expressions are encoded by Rabin's fingerprinting method [21] and stored in the DHT. The concatenation property allows the fingerprints to be computed incrementally and facilitates fragment lookup.

Garces-Erice et al. [22] built a hierarchy of indexes using a DHT containing query-to-query mappings such that a user can look up more specific queries for a given broader query, thereby refining his or her interests. Skobeltysn et al. [23] proposed a path-based distributed index for XPath queries. Paths are hashed to obtain keys that are then stored in a structured overlay. Path queries with "/" and "\*" are processed by a lookup on a query fragment that only contains "/" axis, and then, issuing a broadcast to certain other peers to match the remaining portion of the query. Recently, Abiteboul et al. [24] proposed the KadoP system that supports holistic processing of XPath queries and is built atop a DHT. Their indexing scheme is a combination of an inverted index on XML tags and hierarchical indexes to store the positional representation of instances of the tag name. A holistic twig join algorithm [4] is executed after fetching the contents stored for each query node.

Koloniari et al. [25] proposed the use of multilevel bloom filters to summarize XML documents. The underlying overlay network is based on network proximity and content similarity among peers. Only linear path queries are handled by their system. XTreeNet [40] is a query dissemination engine and constructs query dissemination trees for routing queries to publishers. Queries are locally executed at the publishers and matching documents are returned.

Providing transactional semantics in P2P systems has been a recent topic of interest [26], as existing distributed protocols cannot scale in large dynamic environments. We do not deal with transactional semantics in this work.

## 2.1 Key Motivations

Most of the previous work uses a kind of path summarization technique for indexing XML documents in a P2P environment. Essentially, a complex XPath expression is first broken into simple paths. Each simple path is separately looked up in the P2P network to find the candidate documents and peers. The intersection of the results for each simple path denotes the final result. Such an approach can potentially increase the number of node hops when locating documents. As a result, a summarization technique that allows a query to be processed *holistically*—even in the presence of "/" and "\*"—is necessary.

Load balancing is a challenge when inverted lists are maintained. If a tag appears frequently in the data, then its list can become very large. A peer storing such a list would spend more resources to store it. Moreover, this peer will be overloaded if that tag is frequently accessed. Splitting-and-replication of data summaries [9] can avoid extra lookups but consumes more resources, and requires maintenance and extra effort to keep replicas consistent on updates. It is

also unclear how this approach would scale when peers can join and leave at anytime.

Rather than storing the entire list of document summaries for an XML element tag on one peer, *psiX* builds a hierarchical index on these summaries (i.e., signatures), and the index nodes are distributed across a set of peers. A similar approach has been used by KadoP [24]. However, in KadoP, "\*" wildcards in queries are ignored during processing. Another shortcoming is that the number of DHT lookups depends on the number of nodes in the query. Although parallel lookups can reduce the response time for queries with many nodes, they still increase the network traffic.

Our *psiX* system *summarizes documents* to quickly test the existence of a query pattern in them. The algebraic signatures are indexed. A query is matched in a holistic way, and the number of DHT lookups is *independent* of the number of nodes in a query. Our hierarchical indexes accommodate concurrent write operations by different peers and maintain themselves gracefully.

## 3 OUR SIGNATURE SCHEME

The concept of document signatures or fingerprints has been well studied by the information retrieval community. In this paper, we present a novel signature scheme that is specifically designed for quickly testing the existence of a query pattern in an XML document. In our scheme, XML documents are summarized and mapped into algebraic signatures. A query pattern is also mapped into an algebraic signature. We also describe how a pattern match can be found using the signatures of the documents and queries.

### 3.1 Polynomials over Galois Field

Under the *psiX* system, signatures of both documents and queries are constructed based on irreducible polynomials over a finite field [27], so that algebraic operations can be performed on the signatures for indexing and query processing purposes. Similar to prime numbers in a set of integers, irreducible polynomials over a finite field are polynomials that cannot be represented by a product of two or more nontrivial polynomials of degree greater than zero. A finite field or Galois Field of modulo 2 (denoted by GF(2)) has two elements 0 and 1. In this field, the addition and multiplication operations are equivalent to bitwise XOR and AND operations, respectively. Namely,  $0 + 0 = 1 + 1 = 0$ ,  $1 + 0 = 0 + 1 = 1$ ,  $0 \times 0 = 1 \times 0 = 0 \times 1 = 0$ , and  $1 \times 1 = 1$ . An irreducible polynomial in GF(2) can be represented by a fixed-length bit string, each bit of which represents the coefficient of a polynomial term. Generally, a polynomial of degree  $n$  over a GF(2) is given by  $a_0x^n + a_1x^{n-1} + \dots + a_n$ , where each  $a_i$  is either 0 or 1. This polynomial can be stored in  $\lceil \frac{n+1}{8} \rceil$  bytes.

Polynomials in a finite field have been well studied in the number theory discipline and have properties similar to integers. In particular, operations such as addition, multiplication, least common multiple (LCM), and greatest common divisor (GCD) can be applied to these polynomials [27]. For example, addition of two polynomials in GF(2) is equivalent to performing a bitwise XOR of their corresponding bit string representations. For a given

product of irreducible polynomials, the presence of any particular irreducible polynomial in the product can be tested by a polynomial division. This is because irreducible polynomials behave like prime factors. These convenient properties form the basis of our indexing and query processing strategy. For a given XML document and a query pattern, the occurrence of the query pattern in the document can be determined by *dividing the signature of the document by the signature of the query*.

### 3.2 Benefits of Irreducible Polynomials

In our scheme, signatures of documents are a product of irreducible polynomials. Rather than storing a signature as a list of irreducible polynomials each using fixed-length words, we represent it as a single polynomial (using product) to be space efficient. One may argue that prime numbers could be used instead, but there are some issues. To organize signatures in a hierarchical index, a way to measure similarity between signatures is necessary. The measure we propose is based on identifying common factors between signatures. However, there is no efficient algorithm for factorizing large numbers. On the contrary, factorization of polynomials in finite fields can be done efficiently using randomization [27]. (We show in Section 4 that this factorization step can be avoided by choosing irreducible polynomials of the same degree. This optimization would not be possible if primes were used.) Moreover, irreducible polynomials can be easily generated [28]. They can be represented and manipulated fairly easily by binary strings and binary operations.

### 3.3 Signatures for XML Documents

We first consider only the elements and attributes, and their structural relationship for signature generation. Subsequently, in Section 5.4, we describe how values are handled. To capture the structural summary of a document in a polynomial signature, we first define the *structural summary graph (SSG)* of a document.

**Definition 1 (Structural Summary Graph).** *Given an XML document  $T$ , its structural summary graph  $SSG(T)$  is a directed graph  $G = (V, E)$ , where the vertex set  $V$  denotes a set of distinct tags in  $T$ , and a directed edge from  $v_1$  to  $v_2$  exists in  $G$ , if and only if, the tag corresponding to  $v_1$  is a parent of the tag corresponding to  $v_2$  in  $T$ . The vertex corresponding to the root of  $T$  has a dummy incoming edge.*

Note that an SSG can be constructed for a collection of document trees that have the same root. A dummy incoming edge is added to deal with a special case when a document contains just a single node. For a document that has a schema (or DTD), its SSG can be constructed from the schema (or DTD). For a schema-less document, its SSG can be constructed by parsing the document itself. An SSG generated by parsing a document is a subgraph of the SSG that would be produced directly from the document's schema (or DTD). (Note that a document conforming to a DTD/schema may only have a subset of element names and attributes from the DTD.) An SSG can form a tree or a (cyclic or acyclic) graph depending on the characteristics of a document. For illustration, two SSGs  $S_1$  and  $S_2$  for document trees  $T_1$  and  $T_2$ , respectively, are shown in Fig. 1.




Fig. 1. XML documents and their SSGs. (a) Tree  $T_1$ . (b) SSG  $S_1$ . (c) Tree  $T_2$ . (d) SSG  $S_2$ .

The constructed SSG resembles a backward simulation of the input document tree [29].

Next, we describe how irreducible polynomials are used to map an XML document into a *polynomial signature*, which is essentially a product of irreducible polynomials. To begin with, we assume that each edge in an SSG is assigned a distinct polynomial. (A method is proposed in Section 5.1.)

Given a document tree  $T$  and an SSG  $S$ , we use the notation  $sig(T, S)$  to represent the signature of  $T$  with respect to  $S$ , or  $s$  for short whenever obvious. A *valid* signature is a nonzero bit string that represents a product of irreducible polynomials. If  $T$  does not conform to  $S$ , then  $sig(T, S) = 0$ , because the signature of  $T$  is invalid. Unless otherwise stated, all signatures that we refer to in subsequent discussions are valid.

The process of mapping an XML document into a polynomial signature is described in Algorithm 1. Assuming that an input document tree  $T$  conforms to an SSG  $S$ ,  $T$  is traversed in preorder. A partial signature  $s$  is initialized to a polynomial assigned to the dummy incoming edge in SSG  $S$  (Line 1). If  $T$  has only one node (i.e.,  $|T| = 1$ ), then the partial signature  $s$  becomes its ultimate signature. During the preorder traversal of  $T$ , each time an edge  $e_T$  (associated with a parent-child pair) appears at a certain level (set by the depth of the parent tag in  $T$ ) for the first time, the partial signature  $s$  is updated by multiplying itself with the polynomial assigned to the directed edge  $e_S$  in  $S$  corresponding to  $e_T$  (Lines 3-7). (Note that the source (tag) of  $e_S$  is identical to the parent tag in  $e_T$  and the sink (tag) of  $e_S$  is identical to the child tag in  $e_T$ .) If  $e_T$  appears at  $k$  different levels in  $T$ , then the polynomial assigned to  $e_S$  is multiplied with the partial signature  $k$  times. By using the level information, signatures of XML documents with recursive tag names are made more precise.

#### Algorithm 1. Polynomial Signature Generation

**procedure** *GenerateTreeSignature*( $T, S$ )

/\* $T$  - XML document tree;  $S$  - SSG of  $T^*$  /

1: polynomial  $s \leftarrow p_{dum}$ ; /\* given to the dummy edge in  $S^*$  /

2: **if**  $T$  has one node **then return**  $s$ ; /\* signature \*/

/\* Traverse the document in preorder. \*/

3: **for each** edge  $e_T$  in  $T$  **do**

4:   let  $l$  denote the level at which the parent tag in  $e_T$  appears in  $T$

5:   **if** edge  $e_T$  appears at level  $l$  for the first time **then**

6:     let  $p$  be the polynomial assigned to the directed edge  $e_S$  in  $S$  corresponding to  $e_T$

7:      $s \leftarrow s \times p$

end

end

8: **return**  $s$ ; /\* signature of the document \*/

**Example 1.** We shall construct signatures for the two XML document trees shown in Figs. 1a and 1c. Edges of  $S_1$  are assigned distinct polynomials  $p_0$  to  $p_4$ , and edges of  $S_2$  are assigned distinct polynomials  $r_0$  to  $r_6$ . By applying Algorithm 1, we compute  $\text{sig}(T_1, S_1) = p_0 p_1 p_2 p_3 p_4$ , and  $\text{sig}(T_2, S_2) = r_0 r_1 r_2 r_3^2 r_4 r_5 r_6$ . Identical edges appearing at different levels from the root are accounted for by our algorithm. Hence,  $r_3^2$  appears in  $\text{sig}(T_2, S_2)$ . Note that  $\text{sig}(T_1, S_2) = \text{sig}(T_2, S_1) = 0$ , because  $T_1$  does not conform to  $S_2$ , and  $T_2$  does not conform to  $S_1$ .

Our signature scheme is flexible because the precision of document signatures can be improved by making the structural summaries more accurate. For instance, consider a document, say  $D_1$ ,  $\langle A \rangle \langle B \rangle \langle C \rangle \langle /C \rangle \langle /B \rangle \langle B \rangle \langle D \rangle \langle /D \rangle \langle /B \rangle \langle /A \rangle$ . Consider another document, say  $D_2$ ,  $\langle A \rangle \langle B \rangle \langle C \rangle \langle /C \rangle \langle D \rangle \langle /D \rangle \langle /B \rangle \langle /A \rangle$ . Using Algorithm 1,  $\text{sig}(D_1, S_1) = \text{sig}(D_2, S_1) = p_1 p_3 p_4$ . However, if a polynomial  $p_5$  is multiplied to the signature when  $C$  and  $D$  appear as siblings, i.e., children of  $B$ , then  $\text{sig}(D_2, S_1)$  becomes more precise.

### 3.4 Signatures for Twig Queries

Recall that it is of our interest to find documents with structural matches that can be formulated by XPath expressions given in XQuery queries. Because an XPath expression can be mapped to one or more twig patterns, we directly deal with twig pattern queries. Essentially, a *twig pattern* has a defined structure on the nodes in the pattern, and each node has a label associated with it. A twig pattern can be mapped to an equivalent XPath expression.

#### 3.4.1 Twig Queries with Parent-Child Edges

We shall first deal with twig patterns that have only parent-child edges and can occur anywhere in the document. Such a twig pattern can be represented as a labeled tree. Suppose we have a twig pattern  $Q$  that is a labeled tree with more than one node (i.e.,  $|Q| > 1$ ). Assuming that  $Q$  conforms to an SSG  $S$ , we can generate  $\text{sig}(Q, S)$  by applying Algorithm 1, but with Line 1 in the algorithm replaced by the statement  $s \leftarrow 1$ . On the other hand, if a twig pattern  $Q$  consists of only a single node (i.e.,  $|Q| = 1$ ), this query needs to be handled differently, because there is no edge present in the query. The signature of a singleton query  $Q$  is a list of irreducible polynomials assigned to the incoming SSG edges for the node in  $Q$ . If  $Q$  does not conform with  $S$ , then  $\text{sig}(Q, S) = 0$ .

**Example 2.** Let us compute the signatures for the twig patterns in Figs. 2a and 2b, using the SSGs  $S_1$  and  $S_2$  in Fig. 1. By applying Algorithm 1 to  $Q_a$  and  $Q_b$ , we obtain  $\text{sig}(Q_a, S_1) = p_1 p_2 p_3 p_4$ , and  $\text{sig}(Q_b, S_2) = r_3 r_4$ .  $Q_c$  has one node and its signature is a list, i.e.,  $\text{sig}(Q_c, S_2) = \{r_1, r_6\}$ .

#### 3.4.2 Handling Twig Queries with “//” and “\*”

When  $Q$  has “//” and “\*”, the query signature is a list of signatures. The basic idea to construct signatures for such a




Fig. 2. Twig patterns. (a) Twig  $Q_a$ . (b) Twig  $Q_b$ . (c) Twig  $Q_c$ . (d) Twig  $Q_d$ .

query is to resolve “//” and “\*” by examining the SSG, but not the data. Suppose we need to compute the signature of  $A/B//C/D$ . The partial signature for  $A/B$  is computed. Then, in the SSG, we determine each incoming edge to  $C$  via which  $C$  is reachable from  $B$ .<sup>1</sup> The polynomial assigned to such a qualifying incoming edge is multiplied with the partial signature of  $A/B$ , thereby resulting in a list of signatures. Each signature in the list is then multiplied with the polynomial assigned to the edge from  $C$  to  $D$  in the SSG. To handle a query  $A/B/*C/D$ , we only consider those qualifying incoming edges to  $C$  that belong to (directed) paths of length 2 from  $B$  to  $C$ . We show in Section 3.5 that considering only the incoming edges is enough, instead of considering entire paths when resolving “//” and “\*.”

**Example 3.** Consider twig  $Q_d$  in Fig. 2d. The partial signature of  $M/O$  is  $r_3$ . To resolve “//,” the only incoming edge reachable from  $O$  to  $M$  is edge  $QM$ . Thus, we have a list of signatures  $\{r_3 r_6\}$ . Finally, we multiply each signature in this list with  $r_3$ . Thus,  $\text{sig}(Q_d, S_2) = \{r_3^2 r_6\}$ .

### 3.5 Finding a Twig Match

We begin with a theorem that states a *necessary condition* for a twig pattern to have a match in an XML document by examining their corresponding signatures. First, we consider the case when a twig pattern has more than one node can appear anywhere in the document, and has only parent-child edges. (Proofs of all theorems are provided in the extended version of this paper [30].)

**Theorem 1.** Given an XML document tree  $T$  and a twig query tree  $Q$  ( $|Q| > 1$ ), and suppose  $T$  and  $Q$  both conform to an SSG  $S$ . If  $Q$  is a subgraph of  $T$ , then  $\text{sig}(Q, S)$  divides  $\text{sig}(T, S)$ .

As mentioned in Section 3.4, if  $Q$  has exactly one node or contains “//” or “\*,” then  $\text{sig}(Q, S)$  is a list of signatures.

**Theorem 2.** Given  $\text{sig}(Q, S) = \{s_1, s_2, \dots, s_n\}$ , if  $Q$  has a match in an XML document tree  $T$ , then for  $(1 \leq i \leq n)$ ,  $\exists i$ , s.t.  $s_i$  divides  $\text{sig}(T, S)$ .

In order to compute a signature for a query with “//” (or “\*”) such as  $A//D$ , it is sufficient to consider only the incoming edges to  $D$  reachable from  $A$  in the SSG. This is because, if  $D$  is a descendant of  $A$  in a document, then the polynomial assigned to at least one of the incoming edges to  $D$  (reachable from  $A$ ) (in the SSG) will be present in the document signature. Thus, we do not consider all the distinct (minimal) paths from  $A$  to reach  $D$ . Hence, testing

1. Depth-first search can be used to test reachability.

for the existence of these polynomials (by division) is enough if  $A/D$  appears in the document.

Because Theorems 1 and 2 are themselves a necessary condition for a twig match, false matches may occur, but there are no *false dismissals*. Hence, *recall is always one*. We evaluated the precision of the polynomial signatures using SSGs and observed that our scheme yielded very high precision in all cases. We also constructed signatures by purely considering the distinct tags in documents and queries, and measured their precision. These results are reported in Section 6.

## 4 INDEXING DOCUMENT SIGNATURES

We propose a collection (or forest) of hierarchical indexes for storing document signatures. We call each index and the collection *H-index*. Our goal is to perform the divisibility tests (Theorems 1 and 2) on a subset of document signatures, by ensuring no false dismissals. We shall first describe a local index.

### 4.1 H-Index

For each distinct XML element tag in a document, the document signature is stored in an *H-index* maintained for that tag. (This is similar to the inverted-index scheme [9] that stores, for each distinct XML element tag, the unique paths from the root to that element.) Each node in an *H-index* contains entries of the form  $(sig, ptr)$ . In a nonleaf node, *ptr* is a pointer to a child node in the index, and *sig* is the LCM of all the signatures in the child node. In a leaf node, *ptr* denotes a docid and *sig* is a document signature. What the *containment property* is to the R-tree index [31] is the *divisibility property* to the *H-index*, which is stated next.

**Remark 1.** Let  $s_{parent}$  denote the signature in a node entry.

Let  $s_{child}$  denote a signature in the child node pointed by the node entry. If a query signature  $s_q$  divides  $s_{child}$ , then  $s_q$  divides  $s_{parent}$ .

Remark 1 provides strong leverage to the pruning strategy for query processing, because if a query signature  $s_q$  does not divide a signature in a node entry, then this implies that none of the signatures in the child node are divisible by  $s_q$ .

#### 4.1.1 Finding Relevant Documents

Given a query signature  $s_q$ , the goal is to find all document signatures in the index that are divisible by  $s_q$ . The *H-index* for the target node in the query is first determined. The search begins by first fetching the root node of this *H-index*. For each entry in the node, if its signature is divisible by a query signature  $s_q$ , then the child node of the entry is fetched, and the divisibility test is performed again for the signatures stored in this child. This process continues recursively until a leaf node is reached. For each  $(docsig, docid)$  pair stored in the leaf node, if  $s_q$  divides *docsig*, then *docid* is returned as a candidate. The search process may traverse along multiple paths in the index to find all the relevant document signatures. If the query signature is a list, then a child node is searched further if at least one signature in the list divides a node entry's signature.

### 4.1.2 Inserting a Document Signature

A document signature is inserted into an *H-index* by traversing the index from the root. At each nonleaf node, an entry, whose signature has the highest similarity with the input document signature, is chosen as the best child. Consequently, similar document signatures are placed close to each other in an *H-index*, and the corresponding documents are expected to contain common twig patterns. In a P2P environment, this clustering property plays a vital role, because similar document signatures end up being stored across a few peers, and thereby minimize the time required to locate relevant XML documents.

### 4.1.3 Measuring Similarity between Signatures

Given a pair of document signatures, we can estimate the similarity between the two corresponding documents using the algebraic properties of the signatures. The intuition is that XML documents with similar structure and tag names would share common edges from their SSG, and their signatures would share common irreducible polynomials assigned to the edges in the SSG. Therefore, counting the number of irreducible polynomials common to a pair of signatures provides a sense of similarity between their document structures. Below, we define a similarity measure called *PSim*.

**Definition 2 (PSim).** Given polynomial signatures  $s_a$  and  $s_b$ , let  $g$  and  $l$  denote the number of irreducible polynomials in  $GCD(s_a, s_b)$  and  $LCM(s_a, s_b)$ , respectively.  $PSim(s_a, s_b)$  is defined as the ratio  $\frac{g}{l}$ .

**Example 4.** Let  $p_0, p_1$ , and  $p_2$  be irreducible polynomials. Suppose  $s_a = p_0 p_1^2 p_2^3$  and  $s_b = p_1 p_2^2$ . Then,  $GCD(s_a, s_b)$  has three irreducible polynomials (i.e.,  $p_1 p_2^2$ ), and  $LCM(s_a, s_b)$  has six irreducible polynomials (i.e.,  $p_0 p_1^2 p_2^3$ ). Thus,  $PSim(s_a, s_b) = 0.5$ .

Based on Definition 2, a higher value of *PSim* denotes a higher similarity between two signatures. Note that *PSim* resembles the Jaccard index for measuring the similarity of sets [30].

**Remark 2.** Given two signatures  $s_a$  and  $s_b$ , and if all the irreducible polynomials of  $s_a$  and  $s_b$  have the same degree, then  $PSim(s_a, s_b)$  is computed by  $\frac{deg(GCD(s_a, s_b))}{deg(LCM(s_a, s_b))}$ .

This remark provides a significant opportunity of optimization for determining document similarity. That is, if all the irreducible polynomials assigned to edges in an SSG are of the same degree, then *PSim* can be computed by computing the polynomial degrees, without incurring a potentially costly factorization step.

Such an assignment of polynomials is feasible, because the number of irreducible polynomials of degree  $n$ , denoted as  $C(n)$ , is about  $(\frac{1}{n})$ th the number of all polynomials of degree  $n$  [27]. For example,  $C(17) = 7,710$ , which is enough for an SSG with a modest number of distinct edges.

## 5 COPING WITH A P2P ENVIRONMENT

In this section, we present our main design principles to cope with a peer-to-peer environment, which include

signature generation and indexing document signatures using *H-indexes*. Since *psiX* is built on top of Chord [7], a popular DHT framework, it inherits the benefits of Chord (e.g., scalability, load balancing, and robustness).

### 5.1 Signature Generation Using SSGs

An SSG can be constructed from a DTD, or by parsing the document once if it is schemaless. (Hereinafter, we shall only use the term *SSG*.) In order to assign irreducible polynomials to the edges in an SSG, each peer uses the same algorithm<sup>2</sup> to generate all the irreducible polynomials of degree  $n$ —the value  $n$  may be chosen by the bootstrap (first) peer or is publically known for that P2P environment. Then, given an SSG  $S$ , it is traversed in depth-first order. For each encountered edge  $e$  in  $S$ , a path from the *dummy* tag up to the sink tag of  $e$  is constructed. This path is hashed to an offset  $i \in [1, C(n)]$  by using, for example, a combination of Rabin’s fingerprinting method [21] and the universal hash functions [32]. Recall that  $C(n)$  is the total number of irreducible polynomials of degree  $n$  in  $GF(2)$ . The polynomial at offset  $i$  in the list of irreducible polynomials is then assigned to edge  $e$ . The signature is computed using Algorithm 1.

If an SSG is public (e.g., *dblp.dtd*), then a peer can construct signatures for XML documents that conform to the SSG, or for twig queries on such XML documents. However, if the SSGs of the data (or DTDs), which are much smaller than the actual data, are not public, then they should be advertised (e.g., via the Internet) so that other peers can issue queries to locate such data. The incentive to a publisher, for doing so, is that other peers can now search its data. Thus, given a query, a peer constructs signatures based on the SSGs that it is aware of and are relevant to the query. (The signature for the query can be a list.) For example, a query `//author/name` may be relevant to *dblp.dtd*, *books.dtd*, and an SSG of a schemaless document. Our system is particularly suited for an environment where peers are willing to share their DTDs using a Web site such as <http://xml.coverpages.org>.

### 5.2 Signature Generation without SSGs

If a publisher does not want to publish SSGs for its documents, then *less precise* document signatures and query signatures can be constructed, by assigning irreducible polynomials solely based on tag names. For a document, each distinct tag is hashed to an irreducible polynomial, and their product is the document signature. These signatures, thus, ignore the structural relationship between tag names. For example, a document with two nodes A and B has the same signature, whether A is a parent or child of B. Note that we consider individual tag names instead of tag pairs in order to support queries such as `A//B`. (Koloniari and Pitoura [25] also use distinct XML tags to construct multilevel bloom filters on XML documents for linear path queries.)

A publisher can insert such signatures into the same *H-indexes*. A peer can construct a query signature by considering the distinct tags in it and lookup these indexes. We measured the precision of signatures constructed without the knowledge of SSGs. We observed that for 16 percent of the DTDs (e.g., *Treebank*), the precision was drastically reduced. (See Section 6.) This reduced precision is a disincentive for a user, and thus, encourages a publisher to

2. In the current implementation of *psiX*, we use an irreducible polynomial generator obtained from the Combinatorial Object Server [28].




Fig. 3. Storing the nodes of an *H-index*. (a) An *H-index*. (b) Chord ring.

advertise the SSG for such documents and construct document signatures using the SSG. This criteria may not be suitable in an environment where peers may be selfish. Dealing with selfish and malicious peers is a future research challenge.

### 5.3 Distributed H-Index

To avoid confusion, we shall use the term *node* to refer to an index node instead of a peer/host in a network. For each distinct XML tag name, an *H-index* is maintained by a collection of peers. Each *H-index* is stored in the Chord DHT. Each Chord peer and key is mapped to a 160-bit identifier. The identifier space forms a ring called the Chord identifier ring. Chord supports *lookup* operations to retrieve the value of a key and *insert* operations to store key-value pairs. Chord allows multiple inserts for the same key and appends the new value to the existing values. For an *H-index*, the *identifier of an index node* is treated as a key, and the *entire content of the index node* as a value. This key-value pair is stored in the DHT. An *H-index* is then maintained and traversed by *insert* and *lookup* operations.

**Example 5.** An *H-index* is shown in Fig. 3a. Each index node is assigned a unique identifier. The root node has id “1,” and its first, second, and third child nodes have ids “2,” “3,” and “4,” respectively. The *ptr* field of each entry in a nonleaf node is a node id of a child node. Each index node is then stored in Chord as a key-value pair, with its node id as the key and the entire node content as the value. Fig. 3b shows the Chord identifier ring, where the dark dots denote the 160-bit identifiers of the peers, and the light dots denote the 160-bit identifiers of the signature index node ids. According to the Chord protocol, a key is stored on the first peer that has an identifier equal to or follows the identifier of the key in the Chord ring. In Fig. 3b, the nodes with id “1” and “4” are stored on peer A, the node with id “2” is stored on peer C, and the node with id “3” is stored on peer B. The index can be traversed by issuing a *lookup* operation for node id “1.” The child node id is obtained from the *ptr* field in the node, and a *lookup* is issued again.

#### 5.3.1 Our Design Rationale

We aim to provide better flexibility to peers while splitting nodes—an improvement over the approach proposed by Viglas [15]. In our system, a peer storing an index node supports only the *lookup* and *insert* operations on that node. This peer can leave the network or fail at any time. It is the responsibility of a publishing peer to successfully complete the insertion and node splitting procedures on an *H-index*. Our system is flexible in the sense that a peer

storing an index node can change during the publishing process. To achieve this flexibility, a few challenges should be addressed. Two peers that attempt to independently split a node and create a new node, should assign the same id to the new node. The index should remain in a consistent state under concurrent operations from peers without using local locking schemes. (The DHT framework does not provide guaranteed consistency for multiple writers.) A publishing peer should be able to proceed with the insertion and splitting procedures, even if the peers that store index nodes change during these procedures. Next, we describe our techniques to address the above challenges.

### 5.3.2 Assigning Identifiers to Index Nodes

We propose a scheme to assign ids to the index nodes in a deterministic fashion. Each id is then hashed by Chord using the SHA-1 algorithm [33] (160 bits). As a result, two index nodes may be assigned the same Chord id, but with a very low probability. Instead, if the SHA-2 algorithm (512 bits) is used, then for all practical purposes, we can ignore the possibility of collisions. (Viglas [15] chooses ids randomly from the Chord identifier space and repicks another id if it has already been assigned.)

The root node of an index is special, and its id is computed based on the XML element name. Consider an *H-index* maintained for XML tag *author*. Thus, its root node id is computed using Chord's hash function  $h(\text{"author"})$ . For other nodes in this *H-index*, we use simple Farey fractions [34]. Suppose a node is assigned an interval  $(\frac{n_l}{d_l}, \frac{n_r}{d_r})$  such that  $\frac{n_l}{d_l} < \frac{n_r}{d_r}$ , where  $n_l$  and  $n_r$  are the nonnegative integers, and  $d_l$  and  $d_r$  are the positive integers. Let  $l$  be its level. In our design, each index node has a header that stores its level and assigned interval. Then, the node's id is computed by Chord's hash function  $h(\text{"author.l.n_l.d_l"})$  that maps a key to a 160-bit identifier with a very low probability of collision. When a node at level  $l$  is split, its interval is split into two nonoverlapping intervals, namely,  $(\frac{n_l}{d_l}, \frac{n_r+n_l}{d_r+d_l})$  and  $(\frac{n_r+n_l}{d_r+d_l}, \frac{n_r}{d_r})$ —a nice property of Farey fractions. The first interval is retained by the original node, and the second interval  $(\frac{n_r+n_l}{d_r+d_l}, \frac{n_r}{d_r})$  is assigned to the newly created node whose id is computed by  $h(\text{"author.l.(n_r + n_l).(d_r + d_l)"})$ . At any level, all the node intervals are contained in the interval  $(\frac{0}{1}, \frac{1}{1})$ . By design, once a nonroot node is created at level  $l$ , it remains at level  $l$ . Also, the left boundary of a node's interval never changes. In an *H-index*, the leaf node is at level 0 and the root node has the highest level. Each time the root splits, its level increases by one, and two child nodes at the previous level are created. The root's interval is fixed at  $(\frac{0}{1}, \frac{1}{1})$  and its child nodes are assigned intervals  $(\frac{0}{1}, \frac{1}{2})$  and  $(\frac{1}{2}, \frac{1}{1})$ , respectively, whose node ids are computed by  $h(\cdot)$ .

Once a node is created, its id never changes. Note that certain attributes in a node header change due to splitting, and hence, the entire header is not used to construct a node id.

### 5.3.3 Document Publishing

For every distinct element in an XML document, a peer inserts the document signature and its identifier into its corresponding *H-index*. Note that a document resides at the publishing peer. We assume that a document identifier

TABLE 1  
Variants of *Insert* and *Lookup* Operations

Operation	Purpose
$insert_U(k, .., op)$ $op = \{NONE, STRICT, REPLACE\}$	update an index node
$insert_S(k, ..)$	split an index node
$lookup_O(k, .., op)$ $op = \{NONE, CHILD, HDR, DIVIDE\}$	fetch specific contents in an index node

contains the IP address of the publishing peer. When a peer issues a query, it receives a set of document identifiers of relevant documents, and then, contacts the publishers of the documents by using the IP addresses. We propose an approach that allows peers to synchronize among themselves during node splits, and this approach ensures that the nodes in the index do not go missing due to concurrent operations by peers. Therefore, successfully inserted document signatures are not lost. Note that although our techniques allow concurrent operations and graceful maintenance of an *H-index*, they should not be regarded as a general-purpose transactional protocol for distributed indexes.

We make an assumption that a peer does not *explicitly* delete an index node. So, an *H-index* never shrinks in terms of the index nodes—once created, the nodes are never deleted or merged together unlike in typical B<sup>+</sup>-tree indexes. Document signatures can be deleted from an index node. Each index node is stored as a value list for a key, and space is not preallocated. When a signature is deleted, the updated value list is written back to the underlying storage by the DHT framework. Therefore, space is not wasted. If a leaf node becomes empty, then it is not deleted from the system. Thus, its node id is still accessible, although its content is empty. The parent signature entry is updated to 1. Future insertions can choose this entry for breaking ties when selecting the best child node.

For the ease of exposition, we assume that the DHT operations, such as *lookup* and *insert* issued to Chord, complete successfully. (In our implementation, we retry on failures.) Peer failures are handled by Chord via replication of keys. (See Section 5.5.) We also assume that the peers are *nonmalicious* and adhere to the protocols described below for insertion and node split. We consider a typical P2P environment where queries from users are more frequent than document publications. In subsequent discussions, we shall frequently refer to a node with id  $k$  as node  $k$ .

**Insertion Protocol.** In *psiX*, we provide peers with three new operations called *insert<sub>U</sub>*, *insert<sub>S</sub>*, and *lookup<sub>O</sub>* on a node id. These are variants of the basic *insert* and *lookup* operations provided by the DHT. These operations are invoked by a peer as part of the insertion protocol. The new *lookup<sub>O</sub>* operation is also used during query processing. These operations are listed in Table 1. Using an *insert<sub>U</sub>* operation, a peer can *update* a signature in a node entry to preserve the *divisibility* property, as well as add a new (*sig*, *ptr*) entry to a node. Using an *insert<sub>S</sub>* operation, a peer can *split* a node. The *insert<sub>S</sub>* operation allows multiple peers to synchronize among themselves when splitting the same full node. Using a *lookup<sub>O</sub>* operation, a peer can fetch only certain contents of an index node, rather than reading the entire node and then extracting the necessary content. Thus,

a peer storing the index node examines it and returns only the necessary contents to a calling peer. Both  $insert_U$  and  $lookup_O$  use an  $op$  parameter that will be explained in the following discussions.

Algorithm 2 describes the case when there is enough room in the index to accommodate a document signature  $s$  with docid  $d$ . Thus, no node splits occur at any levels in the index. Similar to an R-tree, the best child is picked (Line 1), and when the leaf level is reached, the input  $(sig, docid)$  is added (Line 3). (When  $k$  is a leaf node,  $lookup_O$  returns a *null* child in Line 1.) Then, the signature entries along the selected path, from the root to the parent of the leaf node, are updated to preserve the divisibility property (Line 5). (In case of ties when selecting the best child, the entry whose signature has the smallest degree is chosen.)

**Algorithm 2.** Basic insertion protocol without node splits

```

proc  $insertion(k, (sig, docid))$ 
  /*  $k$  - index node id;  $(sig, docid)$  - signature and
  document id; */
1:  $(nodetype, k_{child}) \leftarrow lookup_O(k, sig, CHILD)$ 
2: if  $nodetype = LEAF$  then
  /* Assuming node is not FULL */
3:  $insert_U(k_{child}, (sig, docid), NONE)$ 
else
4:  $insertion(k_{child}, (sig, docid))$  /* Traverse the child
  */
  /* Assuming no node splits at lower levels */
5:  $insert_U(k, (sig, k_{child}), NONE)$  /* Update entry */
end
endproc

```

When an  $insert_U$  operation is issued with the arguments  $k, (s, p)$ , and  $NONE$ , then the peer storing node  $k$  will atomically replace the pair  $(r, p)$  in the corresponding value list with the pair  $(LCM(r, s), p)$ . If such a pair  $(r, p)$  does not exist in this value list, then  $(s, p)$  is appended to this list. Note that multiple peers can issue  $insert_U$  operations on the same node entry whose signature is  $r$ . Their requests will be serialized in the order that they arrive at the peer storing the node.

**Node Splitting Protocol.** A node split protocol is initiated by a publishing peer when a leaf node is full and cannot accommodate a new entry. (In our implementation, a caller of  $lookup_O$  in Algorithm 2 is informed if a node is full through the return value.) In the subsequent discussions, we emphasize that an  $H$ -index remains *well-linked* under concurrent operations.

**Definition 3 (Well-linked).** An  $H$ -index is *well-linked* if the logical links to every index node of the  $H$ -index, including any newly created node, can be found by traversing the signature index from the root.

When a leaf node is full, the publishing peer determines the set of full nodes, from the leaf to a nonleaf node, that need to be split. The peer issues node splits (Algorithms 3 and 4) in a top-down fashion, starting from the topmost nonleaf node, to prepare space before inserting the pair  $(sig, docid)$ . A reinsertion is done from the parent of the highest level node that splits. The splitting is done this way so that when multiple peers fetch the same full node,

they consider the same set of child nodes while partitioning the node entries. If we proceed in the bottom-up fashion, then while splitting an internal node, two different peers may have different newly created child node entries to consider while partitioning the entries in the full node. Hence, the top-down approach simplifies the splitting algorithm.

**Algorithm 3.** Protocol for splitting a nonroot node

```

/* This procedure is called by a peer to split a node */
proc  $splitNode(k, V_1, V_2)$ 
  /*  $k$  - key or node id;  $V_1, V_2$  - partitions of node
  contents; */
1:  $(k', h_{k'}, h_{k_{new}}) \leftarrow f(h_k)$  /* new node id, and headers */
2: let  $t$  and  $s$  denote the LCMs of signatures in  $V_1$  and  $V_2$ 
  respectively
3:  $status \leftarrow insert_S(k', \emptyset, h_{k'}, V_2)$ 
4: if  $status = first$  then
5:  $insert_U(parent(k), (s, k'), NONE)$  /* create link */
6:  $insert_U(parent(k), (t, k), REPLACE)$  /* replace */
7:  $insert_S(k, h_k, h_{k_{new}}, V_2)$  /* update hdr */
else
  /* wait for hdr to change using  $lookup_O(k, HDR)$  */
8:  $await(k's\ header! = h_k)$ 
end
endproc
/* This procedure is executed by the peer responsible for
storing  $r$  */
proc  $insert_S(r, h_{r_{old}}, h_{r_{new}}, V_r)$ 
  /*  $r$  - key or node id;  $h_{r_{old}}, h_{r_{new}}$  - old and new headers;
   $V_r$  - list of entries */
9: if  $r$  does not exist then
10: create a node with id  $r$ , header  $h_{r_{new}}$ , and contents
11:  $V_r$  return  $first$ ; /* first peer */
12: else if  $r's$  header =  $h_{r_{old}}$  then
13: remove  $V_r$  from the value list of  $r$ , set  $h_{r_{new}}$  as  $r's$ 
  header
14: return  $first$ ;
end
15: return  $\overline{first}$ ; /* not the first peer */
endproc

```

**Algorithm 4.** Protocol for Splitting the Root of an  $H$ -index

```

proc  $splitRoot(r, V_{r1}, V_{r2})$ 
  /*  $r$  - root id;  $V_{r1}, V_{r2}$  - partitions of root contents */
1:  $(c_1, c_2, h_{c1}, h_{c2}, h_{r_{new}}) \leftarrow f(h_r)$  /* new node ids and
  headers */
2: let  $l_1$  and  $l_2$  denote the LCMs of signatures in  $V_{r1}$  and  $V_{r2}$ 
  respectively
3:  $status \leftarrow insert_S(c_1, \emptyset, h_{c1}, V_{r1})$  /* try to create left
  child */
4: if  $status = first$  then
5:  $insert_S(c_2, \emptyset, h_{c2}, V_{r2})$  /* create right child */
6:  $insert_S(r, h_r, h_r, V_{r1} \cup V_{r2})$  /* remove root contents
  */
7:  $insert_U(r, (l_1, c_1), NONE)$  /* link to left child */
8:  $insert_U(r, (l_2, c_2), NONE)$  /* link to right child */
9:  $insert_S(r, h_r, h_{r_{new}}, \emptyset)$  /* update root's header */
else

```




Fig. 4. Steps involved during a node split. (a) Before splitting  $k$ . (b) Create a sibling  $k'$ . (c) Update the link to  $k'$ . (d) Remove entries from  $k$  and update sig in  $parent(k)$ .

```
10:   await( $r$ 's header  $\neq h_r$ ) /* wait for a hdr change
      using lookupO */
```

end

endproc

A publishing peer will issue a *lookup<sub>O</sub>* operation with the *NONE* option to fetch the entire full node, because Line 1 in Algorithm 2 does not return the entire node. Analogous to splitting a node in an R-tree, a peer (locally) creates a partition of the node entries of a full node using the *PSim* measure to group similar signatures. Algorithm 3 is invoked for a nonroot node. As described in Section 5.3.2, a new node id and new headers are computed (Line 1). The *insert<sub>S</sub>* operation (Line 3) enables peers that concurrently attempt to split the same index node, to synchronize. The header information of a node and a Boolean handle, returned by a peer that stores the index node, are used.

When a peer issues *insert<sub>S</sub>* on a node  $k$ , then Lines 9-15 are executed by the peer responsible for storing  $k$ . It atomically does the following two steps: 1) If the node id does not exist, it creates the node. It initializes the node's header and content with the new header value and the  $(sig, ptr)$  entries passed by the calling peer, respectively. It returns *first* as the handle. 2) Otherwise, it checks if the header of the node (that it has) is identical to the current header value passed by the calling peer. If so, it removes the  $(sig, ptr)$  entries from the node and updates the header with the new header provided by the calling peer. If the headers do not match, it returns *first* as the handle. (Note that Step 1) enables the creation of a new sibling node and Step 2) enables the removal of entries from a node that split.) The calling peer that received *first* as the handle, proceeds to complete the splitting protocol (Lines 5-7). The *REPLACE* option for *insert<sub>V</sub>* (in Line 6) will replace the old LCM of node  $k$  with its new LCM  $t$  in  $parent(k)$ . This process is illustrated in Fig. 4.

A calling peer that received a *first* handle, waits till the header of the node changes (Line 12). It uses the *lookup<sub>O</sub>* operation with the *HDR* option, which only fetches the header of a node. This lookup operation is performed using an exponential backoff strategy till the header changes. The splitting of a root node is special, and the root id never changes. Algorithm 4 describes the steps involved.

In our splitting protocol, only one peer performs the critical splitting operations on a node, and the remaining peers wait for completion of the splitting operations. By using a handle on a node and awaiting the change of the node's header, peers synchronize among themselves to split a full node. It is straightforward to show that an *H-index*

remains in a *well-linked* state under concurrent split operations by peers [30].

**Remark 3.** Once a document signature is successfully inserted into a leaf node of an *H-index*, it remains in the index, because the index is well-linked under concurrent operations by peers.

### 5.3.4 Special Cases

An *H-index* always remains *well-linked*, but the divisibility property may not hold in the nodes that were involved in the splitting process. Suppose a peer splits a node and updates the parent's signature entry with the new LCM of the signatures in the split node. It is possible for another peer to have updated the parent's signature entry while inserting a document signature  $d$ , after this peer read the parent. Thus, the update could be lost and  $d$  may not be found by traversing the index from the root, although it is present in some leaf node of the index (Remark 3). Similarly, after a peer reads a full node that it decided to split, another peer could have updated a signature in the node while inserting a signature. Such an update may be lost after the node splits. If a peer cannot find a document signature that it successfully inserted by searching from the root, it can delete that signature from the leaf node it inserted into and perform a reinsert from the root. Note that this check is not necessary every time a peer inserts a document signature. The likelihood of missing a signature will be high when node splits occur frequently. This could happen due to small node fanouts and a high rate of publishing.

In another scenario, suppose a peer inserts a signature into a leaf and its parent splits (due to other peers) before it updates the entry (in the parent) chosen for insertion using *insert<sub>V</sub>*. Thus, the chosen entry in the parent could have been moved to another node after splitting. In this case, *insert<sub>V</sub>* (Line 5 in Algorithm 2) on the parent would result in two logical links to the leaf. To avoid this, a calling peer issues *insert<sub>V</sub>* using the *STRICT* option. Thus, when *insert<sub>V</sub>* is invoked on a nonleaf node with an argument  $(s, p)$ , a peer, that is responsible for storing that node, atomically updates the signature only if some pair  $(r, p)$  already exists in the node. Otherwise, the node is unaffected.

Thus, in the current design of *H-index*, after node splits, an entry's signature may not be equal to the LCM of its child node signatures. This discrepancy is resolved when the child node splits, and its parent entry's signature is updated with the LCM. In our experiments, for a fanout of 500 and with 27 percent of peers simultaneously publishing, we observed that no signatures were missed for the queries reported in Section 6.

### 5.3.5 Locating Documents Using an H-Index

Given a query signature  $s_q$ , a peer traverses the corresponding *H-index* for the target node in the query, starting from its root node, using *lookup<sub>O</sub>* with the *DIVIDE* option. The  $(sig, ptr)$  entries in an index node are tested for divisibility with  $s_q$  by the peer storing the node. The *ptr* entries are returned and tested for further traversal. If a leaf-level node is reached, then the matching docids are output. Otherwise, each candidate child node is traversed further. If a query




Fig. 5. Summarizing values in an XML document with and without SSGs.

has “//” or “\*,” then the process of locating documents is the same as above, except that the query signature is a list of signatures, and Theorem 2 is used for the divisibility test.

#### 5.4 Indexing Values in XML Documents

Values in XML documents are summarized using histograms for numeric data and polynomial signatures for textual data. (A text string is hashed to an irreducible polynomial.) For instance, the values  $v_0$  and  $v_1$  in Fig. 5, assuming that they are of the same type, are summarized together (say as  $V$ ), because their elements  $E$  map to the same node in the SSG (dotted arrow on the right). If  $v_0$  and  $v_1$  are numeric, then  $V$  denotes a set of intervals of histogram buckets (constructed for  $v_0$  and  $v_1$ ) that are not empty. If  $v_0$  and  $v_1$  are textual data, then  $V$  denotes the LCM of the hash values of  $v_0$  and  $v_1$ .

The document signature and value summary ( $p_2, V$ ) are considered for indexing. If the SSG is not available, then the irreducible polynomial assigned to tag  $E$  (during signature construction) is chosen, and the pair  $(r_5, V)$  is considered for indexing. (Although, the same can be done when SSGs are available, using the edge polynomials can differentiate the case when  $E$  can have more than one parent in the SSG.) Because tags are already used to identify the  $H$ -indexes, we use irreducible polynomials for value indexes.

Textual and numeric value summaries are indexed using hierarchical distributed indexes called  $tH$ -index and  $nH$ -index, respectively. A separate  $tH$ -index or  $nH$ -index is created based on the irreducible polynomial associated with the value summary. For example, the value summary  $(p_2, V)$  for the XML document in Fig. 5 is indexed by an  $nH$ -index or a  $tH$ -index maintained for polynomial  $p_2$ . The  $H$ -index and the  $tH$ -index are almost similar, except that the index keys (i.e., signatures) are constructed differently. The  $nH$ -index is also similar to the  $H$ -index except that it uses one-dimensional intervals as index keys, and its containment property is like that of an R-tree [31]. These value indexes store both the docid and document signature for each  $(p, V)$  that is indexed in its leaf nodes.

Given a query with a value predicate, this predicate is first examined. For example, to process a query  $/A[E="XML"]$ , if the SSG is available,  $(p_2, \text{hash}("XML"))$  is constructed. Otherwise,  $(r_5, \text{hash}("XML"))$  is constructed. The signature of  $/A/E$  is computed as before. (For numeric value predicates, the operator is also considered.) To process the above query, the  $tH$ -index for  $p_2$  (or  $r_5$ ) is searched. The signatures in the node entries are tested for divisibility with  $\text{hash}("XML")$ . When a leaf entry that is divisible is found, the associated document signature is tested for divisibility with the signature for  $/A/E$ . For a query with a numeric value

predicate, an  $nH$ -index is searched. The query interval is tested with the intervals in the node entries according to the operator in the value predicate.

Currently,  $psiX$  searches a value index if a value predicate is present in an XPath query. Otherwise, an  $H$ -index corresponding to the *target node* in the query is searched. Picking the best index is a future research challenge. We have evaluated queries with value predicates using value indexes and report the results in Section 6.5.4.

#### 5.5 Failure, Joining, and Leaving of Peers

The  $psiX$  system relies on the DHT for managing the failure of peers. For instance, Chord replicates a key (and its value) in some  $r$  immediate successors of the peer responsible for storing the key. If this peer fails, then a replica is fetched from one of its  $r$  successors. The effectiveness of replication has been well studied and evaluated [7], [35]. Joining and leaving of peers is handled using the Chord protocol. A peer could request to delete the documents, that it has published, before leaving the network.

### 6 EXPERIMENTAL EVALUATION

The goal of our experimental evaluation is to test the effectiveness and performance of: 1) our signature scheme and 2) our proposed indexing strategy based on  $H$ -index. (Evaluation of the underlying DHT is not the focus of this work.) We built an inverted index using XML element tags called  $I$ -index, which also stores signatures.  $I$ -index is similar to the inverted index scheme proposed by Galanis et al. [9], except that document signatures are stored as summaries instead of document path summaries. Thus, twig queries can be processed without breaking them into root-to-leaf paths. This is an improvement over path-based summarization techniques. (The optimizations such as split-replicate and split-toss were not implemented.) We focus on a typical P2P scenario, where queries are issued more frequently than document publications.

#### 6.1 Implementation Details

We implemented both  $I$ -index and  $H$ -index in C++, and ran the experiments reported in Sections 6.2, 6.3, and 6.6 on a Linux machine with 2.66 GHz Intel Core 2 Duo processor, 1 GB RAM, and one 250 GB SATA drive.

For the experiments reported in Section 6.4, we used PlanetLab [8], where peers can run on machines that are geographically distributed. Therefore, the network conditions are similar to that of the Internet. Each PlanetLab machine runs on Linux and can be simultaneously used by several users. Through virtualization technology, each user can run programs inside a separate virtual machine called *slice*. The load on the machines and network conditions vary with time, and hence, controlled experiments cannot be performed.

#### 6.2 Evaluation of Signature Precision and Size

##### 6.2.1 Data Sets and Queries

We obtained 36 Document Type Definitions (DTDs) (e.g., Treebank, DBLP, and Sigmod Record) published on the Internet [36], [37], [38]. For each DTD, a set of documents were generated using IBM’s synthetic XML data generator.




Fig. 6. Evaluation of (a) signature precision with and without SSGs, (b) signature size with and without SSGs, and (c) the trade-off between increase in signature size and precision improvement.

In all, our test data consisted of a rich set of heterogeneous XML documents with different characteristics such as depth, fanout, recursive structure, etc. The structural summary graphs were generated using these DTDs, and the edges were assigned irreducible polynomials of degree 17. A total of 6,338 distinct irreducible polynomials were used.

We generated XPath queries for the collected DTDs using the XPath generator provided by the YFilter system [39]. The XPath queries contained nested path expressions, predicates, wildcard "\*", and "/" axis. We did not evaluate a value predicate in a twig, but we considered the attributes in the predicates during structure matching.

For each DTD, an average of 798 documents were generated. The total size of the document collection per DTD was an average of 7.3 MB. An average of 176 queries were generated for each DTD. Signatures were generated for the documents and queries, with and without the knowledge of SSGs, as described in Sections 5.1 and 5.2. For each DTD, we computed the number of falsely matched documents (in the document collection) whose signatures were divisible by a query signature (in the query collection), but did not actually contain the query pattern.

### 6.2.2 Results

The precision values (averaged for each DTD), with and without the knowledge of SSGs, are shown in Fig. 6a. When SSGs were used for signature construction, for 29 DTDs, the precision was 1.0, which indicated that our signature scheme precisely captured the structural characteristics of the documents. The lowest precision value among the DTDs was 0.95. When SSGs were not used, signatures did not capture the structural relationships between tags, and thus, the precision drastically reduced for 16 percent of the DTDs (e.g., 0.49 for Treebank). In Treebank, the same element name can appear at different levels in the document, and so, ignoring the SSG was detrimental. In another case, precision for DBLP dropped

to 0.675. A query `/dblp//mastersthesis[address]` matched a DBLP document that contained paths `/dblp/article/address` and `/dblp/mastersthesis`. For many of the DTDs, the precision was 1.0, even when SSGs were not used, because the queries were constructed according to the DTD.

For each DTD, the average document signature size, constructed with and without SSGs, is shown in Fig. 6b. Overall, the use of SSGs increased the size of the document signatures, but precisely captured structural relationships. The trade-off between the percent increase in the average document signature size and percent increase in precision using SSGs is shown in Fig. 6c. In some cases, the increase in signature size was, in fact, offset by significant improvement in precision. Thus, if a publisher has some knowledge of the queries that can be issued by users, an analysis, such as the above, can help in deciding whether to use (and advertise) an SSG or not.

### 6.3 Signature Construction Cost

We measured the average cost of constructing polynomial signatures using Algorithm 1. For document signatures, the average cost was less than 2 ms. For query signatures, the average cost was less than 0.4 ms. Overall, this cost is small compared to the network latencies, which can be more than 50 ms.

### 6.4 Setup for Evaluation of I-Index and H-Index

For all the subsequent experiments, we used signatures constructed with the knowledge of SSGs. Irreducible polynomials of degree 22 were chosen to yield longer signatures.

TABLE 2  
Insert Workload

Name	Avg. Doc. Size(bytes)	Max. Doc. Size(bytes)	Avg. Sig. Size(bytes)	Max. Sig. Size(bytes)
IW ( $\sigma = 10$ )	920.58	14,726	46.17	464
IW ( $\sigma = \infty$ )	924.87	14,726	46.97	464




Fig. 7. (a) Insert workloads IW (number of docs per DTD). (b) Disk usage on PlanetLab.

TABLE 3  
XPath Queries

ID	XPath query	Indexes and tags used to locate the documents	# of docs matched		# of signatures	total size (in bytes)
			$\sigma = 10$	$\sigma = \infty$		
$Q_1$	<code>//*[@member[email]]/name</code>	<i>H-index, I-index</i> for name	258	300	1	12
$Q_2$	<code>//competency/level[evidence]/description</code>	<i>H-index, I-index</i> for description	219	219	1	12
$Q_3$	<code>//Actor[Name]/Filmography/Movie/Year</code>	<i>H-index, I-index</i> for Year	87	240	1	16
$Q_4$	<code>/FILE//ADVP[TO]/ADJ</code>	<i>H-index, I-index</i> for ADJ	0	0	17	204
$Q_5$	<code>//Quote[Last]/PE_Ratio</code>	<i>H-index, I-index</i> for PE_Ratio	327	300	1	12
$Q_6$	<code>//Date[Year="level 3"]</code>	<i>tH-index</i> for Year	552	300	1	8
$Q_7$	<code>/dblp/article[volume&lt;1]</code>	<i>nH-index</i> for volume	0	0	1	12

6.4.1 Data Sets and Document Signatures

We experimented with two insert workloads (denoted by IW) by choosing a different number of documents for each DTD, based on a normal distribution. The DTDs were sorted lexicographically by their file names. (Thus, `actors.dtd` was the first DTD and `viml.dtd` was the last.) We chose a different standard deviation ( $\sigma$ ) for each normal distribution and denote them by  $\sigma = 10$  and  $\sigma = \infty$  (i.e., uniform distribution). Table 2 shows the average document size, maximum document size, average signature size, and maximum signature size for the two IW workloads. Fig. 7a shows the number of documents for each DTD in IW for the two  $\sigma$  values. The total number of documents in IW for  $\sigma = 10$  and  $\sigma = \infty$  was 4,565 and 3,600, respectively.

6.4.2 Queries

We tested seven different XPath queries that contained “\*,” “//” axis, and value predicates. (See Table 3.) Queries  $Q_1 - Q_3$  demonstrate the case where the performance of *I-index* suffers due to long lists of document signatures. Queries  $Q_4 - Q_5$  demonstrate the case where *H-index* and *I-index* process an identical set of signatures. (The selected *H-index* had just one index node.) Queries  $Q_6 - Q_7$  contain value predicates.

6.4.3 P2P Setup

We chose 11 PlanetLab machines that were geographically distributed across the United States. A P2P network was set up by starting one Chord peer on each machine. (We could have started multiple independent Chord peers on each machine to set up a P2P network with a larger number of peers. This would, however, increase the load on each machine. In addition, this would increase the number of hops per DHT insert/lookup operation, because the number of hops depends on the logarithm of the total number of peers.) The publishing step, using *I-index* and *H-index*, was performed at the same time on PlanetLab on two different slices. This was done to ensure that the slices witnessed the same load and network conditions, but did not directly interfere with each other. The case was similar when queries were executed.

Performance evaluation was carried out by first publishing all the document signatures for the documents in IW. Three peers published the same IW simultaneously. This tripled the total number of documents published for each IW and provided more opportunities to observe index node splits in *H-index*. (The index fanout was fixed at 500.)

Once all the document signatures were published, each query was executed 100 times from a single peer. A query was considered complete, once the global identifiers of the relevant documents were retrieved.

6.5 Performance Evaluation on PlanetLab

Overall, we observed that *H-index* could significantly outperform *I-index* for processing XPath queries, to locate relevant XML documents. While publishing documents, *I-index* was twice faster and consumed less bandwidth than *H-index*. However, *I-index* yielded greater skewness in disk space usage among peers. As a result, a few peers spent considerably more resources than others. We conclude that *H-index* is a better choice in a typical P2P environment, where queries are issued more frequently than document publications.

6.5.1 Disk Usage

Fig. 7b shows 11 peers ranked by disk usage after publishing the insert workloads. The reason that *I-index* yielded a greater skewness of disk space usage among participating peers than *H-index* is because some lists in *I-index* grew very large due to frequently occurring XML tags, even across different DTDs. Peers storing such lists spent more disk space than others. *H-index* avoided this problem by splitting index nodes. For example, when  $\sigma = \infty$ , the maximum disk space consumed on a peer for *I-index* was 3.5 times more than when *H-index* was used.

When four peers published the IW workload simultaneously, *I-index* failed to complete successfully, because one peer ran out of disk space and crashed. This is a significant limitation of *I-index*.

6.5.2 Publishing Performance

Table 4 shows the total publishing time for the two insert workloads. *H-index* required about twice the time of *I-index*, because in *H-index*, both DHT *insert* and *lookup* operations were issued and node splits were performed. (*I-index* issued

TABLE 4  
Publishing Cost

Dataset	<i>I-index</i>	<i>H-index</i>			
	Total time (secs)	Total time (secs)	Total # splits	Avg. node split time (secs)	Avg. blocking time (secs)
$\sigma = 10$	23,208	49,157	155	1.76	1.45
$\sigma = \infty$	16,633	34,199	62	1.47	1.36

TABLE 5  
Bandwidth Consumed during Publishing

Dataset	# of inserts into the indexes	<i>I-index</i>		<i>H-index</i>	
		Data write	Data read	Data write	Data write
$\sigma = 10$	146,265	13.5MB	20MB	23MB	
$\sigma = \infty$	112,671	11MB	12.7MB	14MB	




Fig. 8. Average time taken for locating documents (over 100 runs).

only DHT *insert* operations.) Note that the workloads  $\sigma = 10$  and  $\sigma = \infty$  were published at different times on PlanetLab, but the construction of *H-indexes* and *I-indexes*, for each  $\sigma$ , was started at the same time on two different PlanetLab slices.

The workload  $\sigma = 10$  contained more documents than  $\sigma = \infty$ , and thus, took more time to publish. The number of times the insertion protocol was executed for  $\sigma = 10$  and  $\sigma = \infty$  was 146,265 and 112,671, respectively. The number of index node splits, the average time to split a node (lines 3-7 in Algorithm 3 and lines 3-9 in Algorithm 4), and the average time to block during splitting (line 8 in Algorithm 3 and line 10 in Algorithm 4) are also reported in Table 4. The bandwidth consumed during publishing is reported in Table 5. *I-index* consumed significantly less bandwidth, as it did not require DHT lookups and node splits.

In Chord, when a *lookup* is issued, the caller is returned the peer that stores the requested key. A subsequent insert operation on the same key can specify this peer as a starting point for routing. This reduces the number of hops required for a DHT *insert*. *H-index* used this optimization when a document signature was inserted into an *H-index* as it performed a *lookup* before updating the index nodes. (This optimization was not applied to an *I-index* as it directly issued an *insert*.)

Further, the process of picking the best child, when inserting into an *H-index*, was performed locally at the peer that stored an index node. When an index node was full, a publishing peer fetched the full node to perform the splitting protocol. This fetch could be avoided if the task of splitting a node is assigned to a peer that stores it [15]. This would reduce the bandwidth consumption, but would force the storing peer to remain in the P2P network until the splitting process has been completed successfully.

### 6.5.3 Locating XML Documents

Fig. 8 shows the average time taken (over 100 runs) by *H-index* and *I-index* to locate relevant XML documents for

TABLE 6  
Total Number of Hops Required (1 DHT Lookup = 2 Hops)

Type	$Q_1$	$Q_2$	$Q_3$	$Q_4$	$Q_5$
<i>H-index</i> , $\sigma = 10$	4	6	4	2	2
<i>I-index</i> , $\sigma = 10$	2	2	2	2	2
<i>H-index</i> , $\sigma = \infty$	4	6	4	2	2
<i>I-index</i> , $\sigma = \infty$	2	2	2	2	2

TABLE 7  
*I-Index*: Length of List Processed and Number of Matched Signatures

# of sigs	$Q_1$		$Q_2$		$Q_3$	
	$\sigma = 10$	$\sigma = \infty$	$\sigma = 10$	$\sigma = \infty$	$\sigma = 10$	$\sigma = \infty$
total	1633	1477	1204	1171	1228	841
match	258	300	219	219	87	240

TABLE 8  
Performance of Value Indexes (100 Runs)

ID	Avg. time taken		# of hops	
	$\sigma = 10$	$\sigma = \infty$	$\sigma = 10$	$\sigma = \infty$
$Q_6$	0.69 secs	0.39 secs	6	2
$Q_7$	0.12 secs	0.118 secs	2	2

queries  $Q_1 - Q_5$ . Table 6 shows the number of hops required per query. The XML element tag chosen to select an *H-index* and an *I-index* for processing each query is shown in Table 3. The same tag is used for a query to demonstrate that a hierarchical organization is a better choice for document signatures than a single long list. For  $Q_1 - Q_3$ , *I-index* processed long lists of signatures, among which only a fraction were part of the final result. (The list length processed by *I-index* and the number of matched signatures are shown in Table 7.) For queries  $Q_4 - Q_5$ , *H-index* and *I-index* processed the same set of document signatures. (A selected *H-index* had only one index node and was essentially identical to its corresponding *I-index*.) Both *H-index* and *I-index* returned the same set of documents signatures, and thus, no document signatures were missed due to node splits in *H-index*. The recall was one for queries  $Q_1 - Q_5$ .

For  $Q_1 - Q_3$ , we observed that *H-index* was significantly faster than *I-index*. For example, *H-index* processed  $Q_1$  about seven times and nine times faster than *I-index* for  $\sigma = 10$  and  $\sigma = \infty$ , respectively.<sup>3</sup> The *H-indexes* for the chosen XML tags had undergone node splits during publishing. Although, *H-index* required more hops for index traversal than *I-index* for queries  $Q_1 - Q_3$ , the processing of long lists slowed *I-index* substantially. For example, *I-index* required an average of 5.18 sec to process the list for  $Q_1$  ( $\sigma = 10$ ).

The bandwidth consumed by *H-index* was slightly higher than *I-index* due to accessing the root node of the index. For instance, *H-index* read 6,806 bytes as compared to 6,694 bytes by *I-index* for  $Q_1$  ( $\sigma = 10$ ). Both *H-index* and *I-index* tested for divisibility of signatures with a query signature locally at a peer storing an index node, rather than fetching the node over to a querying peer.

3. The PlanetLab machines that we used had good connectivity and were heavily loaded.




Fig. 9. Scalability of *H-index* by varying the number of peers. (a) Fan out = 150 and (b) Fan out = 300.

For queries  $Q_4 - Q_5$ , the structures of the chosen *H-index* and *I-index* were identical, as the *H-index* did not undergo any index node splits. The number of hops required was identical. Their query processing times are comparable, except for  $Q_4$  ( $\sigma = \infty$ ) where *I-index* required more time. This is attributed to the higher load on the peer that locally tested the signature list for *I-index*. This peer spent an average of 3.29 sec for processing this list.

#### 6.5.4 Value Indexes

Table 8 shows the performance for queries  $Q_6 - Q_7$  using the value indexes built in *psiX*. The average time taken for locating documents (over 100 runs), and the required number of hops is reported. For  $Q_6$ , the *tH-index* for the irreducible polynomial assigned to the incoming edge of Year was used. For  $Q_7$ , the *nH-index* for the irreducible polynomial assigned to the incoming edge of Volume was used. Selecting the best among an *H-index*, *tH-index*, and an *nH-index* for a given XPath query is a future research challenge.

#### 6.6 Scalability of H-Index

To evaluate the scalability of *H-index* for locating documents, we set up a P2P network on one machine and ran up to 300 Chord peers. Only one instance of each insert workload was published. Also, a single *H-index* was built over all the document signatures. We built the *H-index* with a fanout of 150 and 300, respectively. We created a query workload (containing 3,314 queries) by randomly selecting queries from the query sets described in Section 6.2.1. We measured the average number of hops required per query (Fig. 9). We observed that with an increase in the number of peers, the number of hops required increased slowly. This showed that *psiX* inherited the scalability properties of the underlying DHT.

## 7 CONCLUSIONS AND FUTURE WORK

We have presented a new system called *psiX*, built atop a DHT framework, for efficiently locating XML data in a peer-to-peer environment. Each XML document is mapped into an algebraic signature that captures the structural summary of the document. A twig query is also mapped into a signature. By dividing a document signature with a query signature, the existence of a twig pattern can be tested quickly and holistically. This avoids breaking a twig pattern into simpler patterns and issuing separate lookups, which

can be expensive given that the network latencies are a dominating cost. The participating peers in the network collectively maintain a collection of distributed hierarchical indexes over the signatures. Document signatures of structurally similar documents can be effectively grouped together in each index. Our extensive experimental evaluation on PlanetLab shows that *psiX* provides an efficient location service for a variety of XML documents.

In future, we would like to investigate how caching can help improve the performance of *psiX*. We plan to evaluate the performance of *psiX* under different levels of *churn*. We have, so far, assumed that peers are neither malicious nor selfish. We plan to investigate schemes to protect *psiX* in the presence of malicious and selfish peers. Further, privacy issues can arise in *psiX* as peers are encouraged to share their DTDs. These issues will be investigated in future.

## REFERENCES

- [1] R. Overbeek, T. Disz, and R. Stevens, "The SEED: A Peer-to-Peer Environment for Genome Annotation," *Comm. ACM*, vol. 47, no. 11, pp. 47-50, Nov. 2004.
- [2] G. Koloniari and E. Pitoura, "Peer-to-Peer Management of XML Data: Issues and Research Challenges," *SIGMOD Record*, vol. 34, no. 2, pp. 6-17, June 2005.
- [3] Q. Li and B. Moon, "Indexing and Querying XML Data for Regular Path Expressions," *Proc. 27th Very Large Data Bases (VLDB) Conf.*, pp. 361-370, Sept. 2001.
- [4] N. Bruno, N. Koudas, and D. Srivastava, "Holistic Twig Joins: Optimal XML Pattern Matching," *Proc. ACM SIGMOD*, 2002.
- [5] P. Rao and B. Moon, "PRIX: Indexing and Querying XML Using Prüfer Sequences," *Proc. 20th IEEE Int'l Conf. Data Eng.*, Mar. 2004.
- [6] P. Rao and B. Moon, "Sequencing XML Data and Query Twigs for Fast Pattern Matching," *ACM Trans. Database Systems*, vol. 31, no. 1, pp. 299-345, Mar. 2006.
- [7] I. Stoica, R. Morris, D. Karger, M.F. Kaashoek, and H. Balakrishnan, "Chord: A Scalable Peer-to-Peer Lookup Service for Internet Applications," *Proc. ACM SIGCOMM '01*, pp. 149-160, Aug. 2001.
- [8] PlanetLab, <http://www.planet-lab.org>, 2009.
- [9] L. Galanis, Y. Wang, S.R. Jeffery, and D.J. DeWitt, "Locating Data Sources in Large Distributed Systems," *Proc. 29th Very Large Data Bases (VLDB) Conf.*, 2003.
- [10] C. Tang, Z. Xu, and S. Dwarkadas, "Peer-to-Peer Information Retrieval Using Self-Organizing Semantic Overlay Networks," *Proc. ACM SIGCOMM '03*, pp. 175-186, Aug. 2003.
- [11] S. Deerwester, S.T. Dumais, G.W. Furnas, T.K. Landauer, and R. Harshman, "Indexing by Latent Semantic Analysis," *J. Am. Soc. Information Science*, vol. 41, no. 6, pp. 391-407, 1990.
- [12] K. Aberer, A. Datta, M. Hauswirth, and R. Schmidt, "Indexing Data-Oriented Overlay Networks," *Proc. 31st Very Large Data Bases (VLDB) Conf.*, pp. 685-696, 2005.
- [13] H. Jagadish, B.C. Ooi, and Q.H. Vu, "BATON: A Balanced Tree Structure for Peer-to-Peer Networks," *Proc. 31st Very Large Data Bases (VLDB) Conf.*, 2005.
- [14] A. Crainiceanu, P. Linga, A. Machanavajhala, J. Gehrke, and J. Shanmugasundaram, "P-Ring: An Efficient and Robust P2P Range Index Structure," *Proc. ACM SIGMOD '07*, pp. 223-234, 2007.
- [15] S. Viglas, "Distributed File Structures in a Peer-to-Peer Environment," *Proc. 23rd IEEE Int'l Conf. Data Eng.*, pp. 406-415, 2007.
- [16] B. Liu, W.-C. Lee, and D.L. Lee, "Supporting Complex Multi-Dimensional Queries in P2P Systems," *Proc. 25th IEEE Int'l Conf. Distributed Computing Systems*, pp. 155-164, June 2005.
- [17] P. Ganesan, B. Yang, and H. Garcia-Molina, "One Torus to Rule Them All: Multi-Dimensional Queries in P2P Systems," *Proc. Seventh Int'l Workshop Web and Databases*, June 2004.
- [18] C. Sartiani, P. Manghi, G. Ghelli, and G. Conforti, "XPeer: A Self-Organizing XML P2P Database System," *Proc. Int'l Workshop Peer-to-Peer Computing and Databases*, 2004.
- [19] R. Goldman and J. Widom, "DataGuides: Enabling Query Formulation and Optimization in Semistructured Databases," *Proc. 23rd Very Large Data Bases (VLDB) Conf.*, pp. 436-445, Aug. 1997.

- [20] A. Bonifati, U. Matrangolo, A. Cuzzocrea, and M. Jain, "XPath Lookup Queries in P2P Networks," *Proc. Sixth Ann. ACM Int'l Workshop Web Information and Data Management (WIDM' 04)*, pp. 48-55, Nov. 2004.
- [21] M.O. Rabin, "Fingerprinting by Random Polynomials," Technical Report TR 15-81, Harvard Univ., 1981.
- [22] L. Garces-Erice, P.A. Felber, E.W. Biersack, G. Urvoy-Keller, and K.W. Ross, "Data Indexing in Peer-to-Peer DHT Networks," *Proc. 24th IEEE Int'l Conf. Distributed Computing Systems*, pp. 200-208, Mar. 2004.
- [23] G. Skobeltsyn, M. Hauswirth, and K. Aberer, "Efficient Processing of XPath Queries with Structured Overlay Networks," *Proc. Fourth Int'l Conf. Ontologies, DataBases, and Applications of Semantics*, Oct. 2005.
- [24] S. Abiteboul, I. Manolescu, N. Polyzotis, N. Preda, and C. Sun, "XML Processing in DHT Networks," *Proc. 24th IEEE Int'l Conf. Data Eng.*, Apr. 2008.
- [25] G. Koloniari and E. Pitoura, "Content-Based Routing of Path Queries in Peer-to-Peer Systems," *Proc. Ninth Int'l Conf. Extending Database Technology*, pp. 29-47, 2004.
- [26] S. Antony, D. Agrawal, and A.E. Abbadi, "P2P Systems with Transactional Semantics," *Proc. 11th Int'l Conf. Extending Database Technology*, 2008.
- [27] E. Bach and J. Shallit, *Algorithmic Number Theory (Volume 1: Efficient Algorithms)*. MIT Press, 1996.
- [28] F. Ruskey and K. Cattell, "The Combinatorial Object Server," <http://www.theory.csc.uvic.ca/>, 2009.
- [29] T. Milo and D. Suciu, "Index Structures for Path Expressions," *Proc. Seventh Int'l Conf. Database Theory*, pp. 277-295, Jan. 1999.
- [30] P. Rao and B. Moon, "Locating XML Documents in Peer-to-Peer Networks Using Distributed Hash Tables," Technical Report TR-DB-2008-01, Univ. of Missouri-Kansas City, <http://r.faculty.umkc.edu/raopr/TR-DB-2008-01.pdf>, Mar. 2008.
- [31] A. Guttman, "R-Trees: A Dynamic Index Structure for Spatial Searching," *Proc. ACM SIGMOD '84*, pp. 47-57, June 1984.
- [32] J.L. Carter and M.N. Wegman, "Universal Classes of Hash Functions," *J. Computer and System Sciences*, vol. 18, pp. 143-154, 1979.
- [33] D. Eastlake and P. Jones, "US Secure Hash Algorithm 1 (SHA1)," IETF Request for Comments 3174, 2001.
- [34] J.H. Conway and R.K. Guy, *The Book of Numbers*. Springer-Verlag, 1996.
- [35] F. Dabek, M.F. Kaashoek, D. Karger, R. Morris, and I. Stoica, "Wide Area Cooperative Storage with CFS," *Proc. 20th ACM Symp. Operating Systems Principles*, pp. 202-215, Oct. 2001.
- [36] The Niagara Project, <http://www.cs.wisc.edu/niagara/>, 2009.
- [37] UW XML Repository, [www.cs.washington.edu/research/xmldatasets](http://www.cs.washington.edu/research/xmldatasets), 2009.
- [38] XML.org, <http://www.xml.org/xml>, 2008.
- [39] Y. Diao, M. Altinel, M.J. Franklin, H. Zhang, and P. Fischer, "Path Sharing and Predicate Evaluation for High-Performance XML Filtering," *ACM Trans. Database Systems*, vol. 28, no. 4, pp. 467-516, 2003.
- [40] E. Curtmola, A. Deutsch, D. Logothetis, K.K. Ramakrishnan, D. Srivastava, and K. Yocum, "XTreeNet: Democratic Community Search," *Proc. 34th Very Large Data Bases Conf.*, pp. 1448-1451, Aug. 2008.



**Praveen R. Rao** received the BE degree in computer engineering from the University of Pune in 1999, and the MS and PhD degrees in computer science from the University of Arizona in 2001 and 2007, respectively. He is an assistant professor of computer science and electrical engineering at the University of Missouri-Kansas City. His research interests include XML indexing and query processing in centralized and peer-to-peer environments, XML filtering and stream processing, and parallel XML data processing. He worked as a software engineer for Amazon.com from August 2001 to August 2002. He is a member of the IEEE Computer Society.



**Bongki Moon** received the BS and MS degrees in computer engineering from Seoul National University, Korea, in 1983 and 1985, respectively, and the PhD degree in computer science from the University of Maryland, College Park, in 1996. He is an associate professor of computer science at the University of Arizona. He received a US National Science Foundation (NSF) CAREER Award in 1999, and currently serves on the editorial board of the *IEEE Transactions on Knowledge and Data Engineering (TKDE)* as an associate editor. He has served on PCs and review panels for numerous conferences and NSF. He was on the research staff for Samsung Electronics and Samsung Advanced Institute of Technology, Korea, from 1985 to 1990. His current research areas of interest include flash memory database systems, XML indexing and query processing, and information streaming and dissemination.

► For more information on this or any other computing topic, please visit our Digital Library at [www.computer.org/publications/dlib](http://www.computer.org/publications/dlib).